

COPES COAT
SPALMATI INDUSTRIALI S.R.L.

COPREN SR120 SP15mm

TOTAL WEIGHT:	1800 gr/m ²	+/- 10%
COMPOSITION:	100% PVC FORMULATED	
THICKNESS:	15 mm	+/- 1 mm
DENSITY:	120 g/lit	+/- 10%
ROLL WIDTH:	100 cm - 140 cm	
ROLL LENGHT:	25 Meter	
COLORS:	Black - White - Grey - Brown (other colors on request)	
APPLICATION:	Gaskets.	

TECHNICAL DATA SHEET:		
BREAKING LOAD (UNI EN ISO 1798:2008)	Longitudinal:	kPa ≥ 250
	Trasversal:	kPa ≥ 250
ELONGATION (UNI EN ISO 1798:2008)	Longitudinal:	% 180
	Trasversal:	% 180
TEAR (UNI 4818 74/9°)	Longitudinal:	Kg 4,0
	Trasversal:	Kg 3,5
SHORE 00	24-26	+/- 15% checked in laboratory at room temperature

Thermoplastic product. Store in a dry place away from the sun.
On request, also available with NON PHTALATE PLASTICIZER (possible traces).
On request, available with one side self adhesive.
Manufactured and formulated in Italy.
In compliance with REACH regulation.
In compliance with RoHS regulation (Direttiva 2011/65/UE): it does not contain Pb, Hg, Cd, CrVI, PBB, PBDE, DecaBDE more than level 0,1%.
Available Safety Data Sheet on request.
Thickness has been checked using measuring equipment issued by certification of calibration , related to accreditation LAT142 released by " Calibration National System" (Legislation nr. 273/1991).

Please note that all information and data are based upon years of experience. However, in view of the wide variety of installation and operating conditions one can not draw final conclusions regarding the behaviour of these materials in all applications. Therefore these data may not be used to support any warranty claims and do not guarantee any level of performance. The user must satisfy himself that the product will work in his intended application before purchasing. When in doubt our staff will be pleased to assist you with samples or in finding the best solution. This information is subject to change without notice.

FORMULATO E PRODOTTO IN ITALIA

 COPES COAT SPALMATI IND.LI Viale della Meccanica ,20 36016 Thiene (VI) Cod.Fisc.e Part.IVA :02373610241 tel 0445 380226- Fax 0445 380227 internet: www.copescoat.it e-mail: info@copescoat.it	Mod.030 rev.00
	SCHEDA TECNICA
	Data emissione 03/03/2017 Data revisione 10/04/2019